

BUEHLER®

Polimet® 1000

VARIABLE SPEED GRINDER/POLISHER

- **Mounts in Laboratory Countertops**
- **Available with either 8" (203mm) or 12" (305 mm) Diameter Platens**
- **Variable Speed Control**
- **Powerful 1Hp (750 W) Motor**
- **Sturdy Aluminum Base**
- **Integral Bowl and Rinsing Sink**
- **Easy-To-Use Control Panel**
- **Built-In Bowl Flush**
- **Pop-Up Water Dispensing Arm**
- **Removable Splash Guard**
- **Built-in Fuse Protection**



Technical Data

The PoliMet® 1000 is a high torque, variable speed grinder-polisher engineered for manual preparation of today's materials. This polisher offers the combination of variable speed and high torque needed for aggressive grinding and polishing.

The conveniently located controls allow the operator to accurately set the polishing speed between 100 and 1200 rpm. The electronic circuitry is designed to maintain the preset wheel speed over any loading conditions encountered in today's laboratories. Speed control ensures greater consistency in preparation time to create the same high quality surface finish from sample to sample.

Ordering Information

Includes one bronze platen, a selection of grinding paper and polishing cloth samples, 10' (3m) power cord with stripped wire ends and operating instructions.

47-2890-160 PoliMet® 1000

12" (305mm) Platen with Sink, 115 VAC, 60 Hz, 1 phase

47-2890-250 PoliMet® 1000

12" (305mm) Platen with Sink, 230 VAC, 50 Hz, 1 phase

47-2895-160 PoliMet® 1000

8" (203mm) Platen with Sink, 115 VAC, 60 Hz, 1 phase

47-2895-250 PoliMet® 1000

8" (203mm) Platen with Sink, 230 VAC, 50 Hz, 1 phase

Specifications

Motor Power:

1Hp (750 W)

Platen Speed:

100 - 1200 rpm

Water Supply:

0.25" (6.35mm) hose, 40-100 psi (2.8-6.9 bar)

Drain Connection:

1" (25mm) hose

Safety Standards:

CE marked, EC applicable directives

Cutout Dimensions

12" (305mm) Platen with Sink

• 17.82" D x 22.83" W (70mm x 90mm)

8" (203mm) Platen with Sink

• 15.88" D x 20.75" W (63mm x 82mm)



The front panel incorporates an on/off toggle switch and platen speed control knob.



The cover keeps debris away from the platen when not in use.



The integral sink and faucet allows fast sample cleaning between steps.

For a complete listing of consumables, please refer to our Consumables Buyer's Guide. Buehler continuously makes product improvements; therefore, technical specifications are subject to change without notice.

© 2010 BUEHLER®, A Division of Illinois Tool Works, Inc. Printed in U.S.A. 25M0506 FN00843 *For metallurgical consumables produced by BUEHLER®



BUEHLER

BUEHLER®, A Division of Illinois Tool Works, Inc.
– Worldwide Headquarters
41 Waukegan Road • P.O. Box 1
Lake Bluff, Illinois 60044-1699 USA
Tel: (847) 295-6500 • Fax: (847) 295-7979
Sales: 1-800-BUEHLER (1-800-283-4537)
www.buehler.com
Email: info@buehler.com



BUEHLER GMBH - European and MESA Headquarters

In der Steele 2 • 40599 Düsseldorf
Postfach 16 03 55 • 40566 Düsseldorf
Telefon: (49) 211 974100 • Telefax: (49) 211 9741079
www.buehler-met.de
Email: info@buehler-met.de

BUEHLER FRANCE

Téléphone: 0800 89 73 71
Télécopie: 0800 88 05 27
www.buehler.fr
Email: info@buehler.fr

BUEHLER UNITED KINGDOM

Telephone: 0800 707 6273
Fax: 0800 707 6274
www.buehler.co.uk
Email: sales@buehler.co.uk

BUEHLER CANADA

10 Carlow Court, Unit #2
Whitby, Ontario L1N 9T7
Telephone: (905) 430-4684
Fax: (905) 430-4647
Sales Telephone: 1-800-268-3593
Email: info@buehler.ca

BUEHLER, ASIA-PACIFIC

5/F Vogue Centre
696 Castle Peak Road
Lai Chi Kok, Kowloon
Hong Kong, SAR, China
Telephone: (852) 2307 0909
Fax: (852) 2307 0233