BUEHLER® SimpliMet® 2

HYDRAULIC SPECIMEN MOUNTING PRESS

- Basic Specimen Mounting Press for Virtually any Materials Engineering Laboratory
- Corrosion and Impact Resistant Molded (RIM) Cabinet
- Manual Pumping Action for Pressure Application
- Direct Reading PressureGauge
- Quick Ram Return to Speed Reloading
- Thermostatically
 Controlled 350 Watt Mold
 Heater
- Accommodates 1", 1¼", 1½", 25mm and 30mm Mold Sizes
- Duplex Mold Produce2 Specimen Mounts at OneTime
- Handle can be Installed for Left or Right Operation
- **CE Marked**





Specifications

20-1410-115 SimpliMet® 2 Hydraulic Specimen Mounting

Press, RIM cabinet containing built-in hydraulic system, pressure gauge, TetraMet® mold closure, finned slip-on cooler and thermostatically controlled mold heater. Includes one pair of heat resistant gloves, one tube of 1¼" (32mm) PreMolds®, samples of Phenolic and EpoMet® powders, release agent, scraper tool and operating instructions. For operation on 115V/60Hz/1 phase. Mold assemblies supplied separately; select from list shown below.

20-1410-220 SimpliMet® 2 Hydraulic Specimen Mounting Press, same as above except for 220-240V/50Hz/1 phase operation.

Dimensions: 11" W x 14" D x 23" H

(279 x 356 x 584mm)

Shipping Weight: 90 lbs. (41kg)

Mold Assemblies

(Includes molding cylinder, upper and lower rams) **20-2104 Mold Assembly,** 1" diameter specimens

20-2105 Mold Assembly, 11/4" diameter specimens

20-2109 Mold Assembly, 1½" diameter specimens

20-2125 Beveled Mold Assembly, 11/4" diameter specimens

20-2126 Beveled Mold Assembly, 11/2" diameter specimens

20-2127 Mold Assembly, 25mm diameter specimens

20-2128 Mold Assembly, 30mm diameter specimens

20-2204 Duplex Mold Assembly, for the production of two specimen mounts at one time, 1" diameter specimens

20-2205 Duplex Mold Assembly, for the production of two specimen mounts at one time, 1¼" diameter specimens

20-2209 Duplex Mold Assembly, for the production of two specimen mounts at one time, 1½" diameter specimens

Accessories

20-2117 TetraMet® Closure, replacement, mold closure for 2" (50mm) OD Buehler® threaded molds with patented non-conductive handles, rapid closing and quick release features

20-2223-115 Automatic Heater, replacement, 350 watt, 2" (50mm) ID, thermostatically controlled with cord and switch for 115V, 50/60 Hz, 1 phase

20-2223-220 Automatic Heater, replacement, same as 20-2223-115 except for operation on 220V, 50/60 Hz, 1 phase

20-2303 Cooler, replacement, slip-on with finned design

20-2323 Cooler, water cooled with fittings for hose connections, 2" (50mm) ID





The SimpliMet[®] 2 Press comes equipped with a thermostatically controlled mold heater (top image) and a slip-on mold cooler (bottom image).

For a complete listing of consumables, please refer to our Consumables Buyer's Guide. Buehler continuously makes product improvements; therefore, technical specifications are subject to change without notice.

© 2006 BUEHLER LTD. Printed in U.S.A. 25M0206 FN00682 Rev. 2

*For metallurgical equipment produced by BUEHLER LTD. USA

BUEHLER GMBH

In der Steele 2 • 40599 Düsseldorf Postfach 16 03 55 • 40566 Düsseldorf Telefon: (+49) 0211/974100 • Telefax: (+49) 0211/9741079 Web Site: http://www.buehler-met.de Email: info@buehler-met.de

BUEHLER SARL

Miniparc de Dardilly, Bát. 0 3, Chemin du Jubin • 69570 Dardilly-France Téléphone: (+33) (04) 37 59 81 20 Télécopie: (+33) (04) 37 59 81 29 Web Site: http://www.buehler.fr Email: info@buehler.fr

BUEHLER UK

101, Lockhurst Lane • Coventry • CV6 5SF Telephone: (+44) (0) 24 7658 2158 • Fax: (+44) (0) 24 7658 2159 Web Site: http://www.buehler.co.uk Email: sales@buehler.co.uk

BUEHLER CANADA

9999 Highway 48 Markham, Ontario L3P 3J3 Telephone: (905) 201-4686 • Fax: (905) 201-4683 Sales Telephone: 1-800-268-3593 Email: info@buehler.ca

BUEHLER ANALYST®

SECTION

BUEHLER ASIA

5/F Vogue Centre 696 Castle Peak Road Lai Chi Kok, Kowloon Hong Kong, SAR, China Telephone: (852) 2307 0909 Fax: (852) 2307 0233



BUEHLER LTD. – Worldwide Headquarters 41 Waukegan Road • P.O. Box 1 Lake Bluff, Illinois 60044-1699 USA Tel: 847/295-6500 • Fax: 847/295-7979 Sales: 1/800/BUEHLER • 1/800/283-4537 Web Site: http://www.buehler.com Email: info@buehler.com 2